

BIT 2nd Year

Semester 3

IT 3505

Web Application Development II

**Fundamentals of Asynchronous
JavaScript and XML (AJAX) –
Part 1**



Introdcution to DOM



What is DOM?

- Document Object Model
 - The web browser builds a *model* of the web page (the *document*). This model is called the **Document Object Model(DOM)** and includes all the *objects* in the page (tags, text, etc.)
 - The developers can access objects in a DOM through the scripting language JavaScript.

This is what the browser reads


```
<html>
  <head>
    <title>Sample DOM Document</title>
  </head>
  <body>
    <h1>An HTML Document</h1>
    <p>This is a <i>simple</i> document.
  </body>
</html>
```

This is what the browser displays

An HTML Document

This is a *simple* document.

The **HTML DOM** model is constructed as a tree of **Objects**:



With this model JavaScript

- can change the HTML elements
- can change the HTML attributes
- can change the CSS styles
- can remove existing HTML elements
- can add new HTML elements
- can react to all existing HTML events
- can create new HTML events

Getting vs. Setting

```
var oldValue =  
    document.getElementById("myID").value;
```

```
document.getElementById("myID").value =  
    "new value";
```

Getting



Setting



Getting vs. Setting

- The `getElementById` Method
 - This is the most common JavaScript method to

```
<html>
<body>

<p id="myID"></p>

<script>
    document.getElementById("myID").innerHTML = "Let's
Learn DOM";
</script>

</body>
</html>
```

gets the content of an element

The getElementById Method

- One can even set the value of an element by using **getElementById** method

```
<!DOCTYPE html>
<html>
<body>

<p id="title">Let's Learn DOM </p>

<p id="myID"></p>

<script>
var x = document.getElementById("title");
document.getElementById("myID").innerHTML = "The value of
element is " + x.innerHTML;
</script>

</body>
</html>
```

DOM EventListener

- This method is used to attach an event handler to the specified element.
- Usage :

```
element.addEventListener(event, function, useCapture);
```

Type of the event

function need to be called

Optional : Boolean value

DOM EventListener

```
<!DOCTYPE html>
<html>
<body>

<button id="myBtn">click</button>

<script>
document.getElementById("myBtn").addEventListener("click", hello);

function hello() {
    alert ("Hello World!");
}
</script>

</body>
</html>
```

DOM EventListener

- You can add multiple eventlisteners of different types or the same type to a single element

```
element.addEventListener("mouseover",  
FunctionOne);  
element.addEventListener("click",  
FunctionTwo);  
element.addEventListener("click",  
FunctionThree);  
element.addEventListener("mouseout",  
FunctionFour);
```

document.write()

- This can be used to write directly to the HTML output stream

```
<!DOCTYPE html>
<html>
<body>

<script>
    document.write(Date());
</script>

</body>
</html>
```

document.write()

```
<html>
  <head>
    <title>DOM Sample 1</title>
  </head>
  <body>
    Information about this document.<br>
    <script type="text/javascript">
      document.write("<br>Title: ", document.title);
      document.write("<br>Referrer: ", document.referrer);
      document.write("<br>Domain: ", document.domain);
      document.write("<br>URL: ", document.URL);
    </script>
  </body>
</html>
```

Information about this document.

Title: DOM Sample 1

Referrer:

Domain:

URL: file:///C:/Users/UCSC/Desktop/demo.htm

DOM Events

- By using JavaScript function can be developed to be invoked
 - When a user clicks the mouse
 - When a web page has loaded
 - When the mouse moves over an element
 - When an input field is changed
 - When an HTML form is submitted

```
<!DOCTYPE html>
<html>
<body>

<p onclick="this.innerHTML='changed'">Click
on this </p>

</body>
</html>
```

This can be any element

Some information about elements

```
<html>
  <head>
    <title>DOM Sample</title>
    <script type="text/javascript">
      function showInfo() {
        var element = document.getElementById("opener");
        var buffer = element.id + " tag is " + element.tagName;
        alert(buffer);
        element = document.getElementById("actionItem");
        buffer = element.id + " tag is " + element.tagName;
        buffer += ", type is "+element.type;
        alert(buffer);
      }
    </script>
  </head>
  <body>
    <p id="opener">The id attribute is very helpful.</p>
    <p id="closer">This is the closing paragraph.</p>
    <form>
      <button id="actionItem" type="button" onclick="showInfo()">Show Info</button>
    </form>
  </body>
</html>
```

Element doesn't refer to the value! Just the element. We have to explicitly ask for the value or the attribute values

Creating elements through Nodes

- Steps
 1. Create the element (element node)
 2. Append it to an existing element

```
<div id="myID">  
<p id="p1">This is a paragraph.</p>  
</div>
```

```
<script>  
var p = document.createElement("p"); //creates a new <p>  
element  
var node = document.createTextNode("Newly, created"); // To add  
text to the <p> element  
p.appendChild(node); //append the text node to the <p> element  
var element = document.getElementById("myID");  
element.appendChild(p); // append the new element to an  
existing element  
</script>
```

Moving forward

- The HTML Document Object Model is a standard for structuring data on a web page
 - The field is advancing rapidly as people recognize the benefits of standardized structure and access
 - The DOM is steadily improving to cover general purpose data structuring requirements
- XML (Extendible Markup Language) also uses the Core DOM to specify its structured data
 - similar to HTML but more carefully defined